

OAK

PENDANT

Oak is a sustainably sourced timber pendant light which emits a delicate luminance. Each Oak Pendant Light shade is hand crafted and defined by the grain of the oak selected. The body of the light is accentuated by the intersecting hole which defines its unique form.

The Oak pendant is available in two sizes and three finishes.

AVAILABLE FINISHES



NATURAL
OAK HARDWOOD

LIMED
OAK HARDWOOD

BLACK
OAK HARDWOOD

TECHNICAL

MATERIAL	OAK HARDWOOD OR BLACKWOOD HARDWOOD	SKU CODES	EG. OKP.S.H-OAK = OAK STANDARD PENDANT IN NATURAL OAK HARDWOOD
LAMPING	OKP.S - 8.5W, E27, 820LM, 3000K, WARM WHITE, DIMMABLE OKP.L - 13W, E27, 1521 LM, 2700K, WARM WHITE, DIMMABLE GLOBES ARE SUPPLIED WITH AUS/NZ ORDERS ONLY E27 LAMP HOLDER IS SUPPLIED FOR 240V REGION. E26 LAMP HOLDER IS SUPPLIED FOR 120V REGION.		OKP.S.H-XXX OAK STANDARD PENDANT OKP.L.H-XXX OAK LARGE PENDANT
		FINISH	NATURAL OAK HARDWOOD (H-OAK) LIMED STAINED OAK HARDWOOD (H-LIM) BLACK STAINED OAK HARDWOOD (H-BLK)
LED LIFESPAN	15,000 HRS		
CONTROL	PHASE CONTROL / NETWORK CONTROL DIMMABLE DIMMING RANGE 10 - 100%. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH AN ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	DIMENSIONS	STANDARD - Ø215 X 260MM / Ø 8.5 X 10.3” LARGE - Ø352 X 425MM / Ø 13.8 X 16.7”
		PRODUCT WEIGHT	4 / 10KG 15 /33LB
		PACKAGING DIMENSIONS	L 300 W 300 H 300 / L 11.8” W 11.8” H 11.8” L 450 W 450 H 450 / L 17.7” W 17.7” H 18.5”
CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE		
CORD	2000 / 7” (STANDARD) OR 3M / 10” (LARGE) BLACK CLOTH AND SUSPENSION WIRE NOTE: LONGER LENGTHS AVAILABLE UPON REQUEST	PACKAGING WEIGHT	5KG / 11LB 18KG /39.7LB
IP RATING	IP20 - FOR INDOOR USE ONLY		
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0		

DIMENSIONS



OKP.S
Ø215 H260
Ø8.5” H10.3”



OKP.L
Ø352 H425
Ø13.8” H16.7”

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE STANDARD CANOPY WILL BE SUPPLIED.

OAK STANDARD



STANDARD - 120MM
SUSPENSION + FLEX CANOPY
CAN.ST.120.SF.X-XXX

Ø120 X 30MM / 4.7” X 1.2”



SLIM
SUSPENSION + FLEX CANOPY
CAN.SL.SF.X-XXX

Ø120 X 7MM / 4.7” X 0.3”



PUCK
SUSPENSION + FLEX CANOPY
CAN.PK.SF.X-XXX

Ø50 X 65MM / 2” X 2.6”

OAK LARGE (EXTERNAL CEILING ANCHOR PROVIDED WITH CANOPY)



STANDARD - 120MM
SINGLE PENDANT + EXTERNAL
CEILING MOUNT CANOPY
CAN.ST.120.SFCM.X-XXX

Ø120 X 30MM / 4.7” X 1.2”



SLIM
SINGLE PENDANT + EXTERNAL
CEILING MOUNT CANOPY
CAN.SL.SFCM.X-XXX

Ø120 X 7MM / 4.7” X 0.3”



PUCK
SINGLE PENDANT + EXTERNAL
CEILING MOUNT CANOPY
CAN.PK.SFCM.X-XXX

Ø50 X 65MM / 2” X 2.6”

TECHNICAL

MATERIAL	ANODISED ALUMINIUM / POWDERCOATED ALUMINIUM
CANOPY FINISH	ANODISED BLACK (A-BLK) ANODISED CLEAR (A-CHM) POWDERCOATED WHITE (C-WHT)
SKU CODES	EG. CAN.ST.120.SF.A-CHM = STANDARD SUSPENSION + FLEX CANOPY IN CHAMPAGNE ANODISED FINISH



BLACK
ANODISED

CHAMPAGNE
ANODISED

WHITE
POWDERCOATED